

## Control Joint With Anti-Fracture Membrane

ES-EJ09

	Drawing No. ES EJ09
LATICRETE® Hydro Ban®	
Treat Closest Joint with Flexible Sealant ——————	
Concrete	
Saw Cut Control Joint (fill co with LATICRETE 254 Platinum, flush with concrete and allow LATICRETE Hydro Ban (Use 6" (150mm) wide strip LATICRETE Waterproofing/Anti- Fabric over control joint) —	of
LATICRETE 254 Platinum	
LATICRETE SpectraLOCK <sup>®</sup> PRO Premium Grout; or, LATICRETE PermaColor™ Grout	
Ceramic Tile or Stone	
	Revision Date: 5/12 Scale: N.T.S.
AS A PROFESSIONAL COURTESY, LATICRETE OFFERS TECHNICAL SERVICES FREE OF CHARGE. THE USER MAINTAINS ALL RESPONSIBILITY OF THE TECHNICAL APPLICABILITY AND SUITABILITY OF THE TECHNICAL	(C)2012 LATICRETE INTERNATIONAL, INC. ALL RIGHTS RESERVED. THE RIGHT TO UTILIZE LATICRETE DETAILS FOR COMMERCIAL PURPOSES IS GRANTED EXCLUSIVELY TO CONTRACTORS, ARCHTEUTS, QUANTITY SURVEYORS, EVGINEERS, AND SPECIFICATIONS WRITERS, LATICRETE (R), LATIAPCAY (R), MAR FEGISTENED TRADELMARKS OF LATICRETE INTERNATIONAL, INC. US &

NOTE: "For complete application information and limitations consult related Product Data Sheets and Execution Statements related to this detail, and applicable industry standards."

